DRAWING NOT TO BE USED FOR CONSTRUCTION

THE STORMCEPTOR SYSTEM IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: United States Patent No. 5,753,115 • 5,849,181 • 6,068,765 • 6,371,690 • 7,582,216 • 7,666,303 | Australia Patent No. 693,164 • 707,133 • 729,096 • 779,401 • 289,647 • 2008,279,378 • 2008,288,900 | Canadian Patent No. 2,009,280 • 2,137,942 • 2,175,277 • 2,180,305 • 2,180,383 • 2,206,338 • 2,327,768 | Indonesian Patent No. 007058 | Japan Patent No. 3581233 • 9-11476 | Korea Patent No. 10-1451593 • 0519212 | Malaysia Patent No. 118987 | New Zealand Patent No. 314,646 • 583,583 • 583,008 | South African Patent No. 2010/00683 • 2010/01796 | OUTLET INLET ACCESS OPENING TO BE ORIENTED OVER OIL CLEANOUT PORT AND RISER PIPE 150ø OII CLEANOUT PORT, TYP. PLAN VIEW -FRAME AND COVER EMBOSSED "STORMCEPTOR" 305 GRADE ADJUSTERS TO SUIT FINISHED GRADE 2438ø 229 TO SUIT FINISHED GRADE 150ø OIL CLEANOUT PORT TO BE RAISED TO
ELEVATION AS CLOSE TO
THE UNDERSIDE OF THE
FLAT CAP (TRANSITION TO 1200mm AS REQUIRED) INI FT 635± OUTLET PIPE, SIZE BASED ON SEWER DESIGN.
FLEXIBLE BOOT OR
GROUTED TO CONCRETE 305 RISER SECTION 1219 762¢ RISER PIPE CONCRETE RISER AND SLAB COMPONENTS C/W RUBBER 1219 GASKETS FOR JOINTS MANUFACTURED TO CSA AND OPS STANDARDS. 762ø WINGED DROP TEE 1219 3048 356 SECTION VIEW **Storm**ceptol THE LEGACION PRINCIPATION OF THE THE LIFE OF THE PROCESSAN AND AND THE LIFE OF THE PROCESSAN AND AND THE LIFE OF THE STATE OF THE LIFE OF



USA 888-279-8826 CA 800-565-4801 INTL +1-416-960-9900

IMBRIUMIPRIVATE/CAD/STANDARD PRODUCT LINE/STORMCEPTOR OSR/OSR - NEW IMBRIUM METRIC TEMPLATE/OSR 6000.DWG 1/6/2015 11:41 AM

| | 001 | 2.0000 | REV# | DATE | REVISION DESCR | RIPTION | BY | SHEET |
|--|----------------|-----------|-------|------------|----------------|------------|--------------|--------|
| | J 051 | R 6000 | | | | | l | NUMBER |
| | STANDARD MODEL | | | | | | | |
| | | | | | | | | 1 |
| | #### | | | | | | | |
| | | | | | | | | OF1 |
| | DATE:####### | SCALE: 60 | PROJE | CT No.: ## | | DRAWN: ### | CHECKED: ### | |